

=====

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

=====

PRODUCT NUMBER: S-655

IDENTITY: **WONDER WIPE**

Revision Date: 4/13/2010

-----

**Section I**

=====

Manufactured For: K & K CHEMICAL COMPANY  
Address: 1303 INDUSTRIAL DRIVE (BOX 737)  
ROYSE CITY, TX 75189

Telephone Numbers:  
Emergency: (800)424-9300 (CHEMTREC)  
Information: (800)958-6921

HMIS CODES: HEALTH: 0 FLAMMABILITY: 3 REACTIVITY: 0 PERSONAL PROTECT: A

-----

**Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION** (All of the ingredients contained in this product are listed on the TSCA inventory.)

=====

Name	CAS No.	OSHA PEL	ACGIH TLV	OTHER LIM %
LINEAR ALCOHOL ETHOXYLATE	34398-01-1	N/A	N/A	N/A

-----

**Section III: PHYSICAL/CHEMICAL CHARACTERISTICS**

=====

Boiling Point:	>150 F	Specific Gravity (water=1)	0.70 (liquid phase)
Vapor Pressure(mm Hg)	110 PSI	Melting Point:	N/A
Vapor Density(AIR=1)	>1	Evaporation Rate:	<1
Solubility in Water:	N/A	Appearance and Odor:	WHITE TOWEL, ETHER ODOR

-----

**Section IV: FIRE AND EXPLOSION HAZARD DATA**

=====

Flash Point(Method Used): <0 F (TCC) Flammable Limits: LEL: 1.0 UEL: 36.0  
Extinguishing Media: DRY CHEMICAL, FOAM OR CO2  
Unusual Fire and Explosion Hazards: VAPORS ARE HEAVIER THAN AIR AND MAY ACCUMULATE IN LOW AREAS OR ALONG THE GROUND.  
Special Fire Fighting Procedures: COOL SURROUNDING CONTAINERS WITH WATER FOG. WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA) WITH FULL FACE SHIELD. SHUT OFF ALL SOURCES OF IGNITION. USE WATER SPRAY TO DISPERSE VAPORS AND PROTECT PERSONNEL.

-----

**Section V: REACTIVITY DATA**

=====

Stability: Unstable:  Stable:  Conditions to avoid: DO NOT STORE IN DIRECT SUNLIGHT. AVOID TEMPERATURES ABOVE 120 DEG F

Incompatibility (Materials to Avoid): STRONG OXIDIZERS, SELECTED AMINES, STRONG ACIDS AND BASES Hazardous Decomposition or Byproducts: NONE KNOWN

Hazardous Polymerization: May Occur:  Will Not Occur:  Conditions to Avoid: NONE KNOWN

-----

**Section VI: HEALTH HAZARD DATA**

=====

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES  
Health Hazards(Acute and Chronic):  
INGESTION: MAY CAUSE NAUSEA.  
EYES: MAY CAUSE HEADACHE  
INHALATION: MAY CAUSE DIZZINESS OR UNCONSCIOUSNESS  
SKIN: MAY CAUSE IRRITATION  
Carcinogenicity: NTP: NO IARC Monographs: NO OSHA Reg: NO  
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE  
Medical Conditions Generally Aggravated by Exposure: NONE KNOWN  
Emergency and First Aid Procedures: EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING. CONSULT PHYSICIAN FOR ANY OF THE ABOVE EXPOSURES.

-----

**Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE**

=====

Steps to be Taken in Case Material is Released or Spilled: WEAR SCBA AND PROPER PROTECTIVE EQUIPMENT. SHUT OFF ALL SOURCES OF IGNITION AND DIKE AREA OF SPILL. KEEP OUT OF WATER SOURCES. CLEAN UP SPILL USING ABSORBENT MATERIAL. TRANSFER TO DOT-APPROVED CONTAINER USING NON-SPARKING TOOLS.  
Waste Disposal Method: DISPOSE OF WASTE MATERIAL IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS. DO NOT DISCARD IN TRASH COMPACTOR.  
Precautions to be Taken in Handling and Storing: DO NOT DROP, REUSE OR REFILL CONTAINER. DO NOT STORE IN DIRECT SUNLIGHT. DO NOT EXPOSE TO HEAT, SPARKS, OPEN FLAME OR TEMPERATURES ABOVE 10 DEG F. DO NOT INTENTIONALLY INHALE VAPORS.  
Other Precautions: NONE

-----

**Section VIII: CONTROL MEASURES**

=====

Respiratory Protection:	SCBA OR ORGANIC VAPOR CANISTER MASK	Ventilation:	Local Exhaust:
Mechanical:	N/A	Special:	N/A
Other:	N/A	Protective Gloves:	BUTYL
Eye Protection:	N/A	Other Protective Clothing or Equipment:	N/A
Work/Hygienic Practices:	N/A		