

H	2
F	2
R	0
P	X

MATERIAL SAFETY DATA SHEET

MANUFACTURER: K & K Chemical Co.
TELEPHONE NO.: (800) 327-0646
ADDRESS: 1303 Industrial Drive, Royse City, TX 75189

PRODUCT: RED FLOAT™
PART NUMBER(S): K-690
MSDS Prepared By: J. Austin Maglothin, Ph.D.
Revision Date: April 13, 2010

SECTION I - GENERAL

Chemical Name & Synonym: Not Applicable
Trade Name & Synonyms: RED FLOAT™
Chemical Family: Petroleum hydrocarbon based mixture
Formula: Trade secret

SECTION II - HAZARDOUS INGREDIENTS

Petroleum hydrocarbons	CAS No.	8042-47-5
Sodium petroleum sulfonate	CAS No.	68608-26-4
Poly(ethylene glycol) 4-nonylphenyl ether	CAS No.	127087-87-0

SECTION III - PHYSICAL AND CHEMICAL DATA

Boiling Point (°C): 162
Vapor Pressure (MM Hg @ 38°C): 5
Vapor Density (Air = 1): 5.0
Specific Gravity (H₂O = 1): 0.782
% Volatile by Volume: Not determined
Evaporation Rate (BUAC = 1): 0.07
Solubility in Water: Insoluble
Appearance and Odor: Dark red fluid with petroleum odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammable Limits (%):
- LEL: 1
- UEL: 6
Flash Point (Method Used): 41.6°C (TCC)
Extinguishing Media: Use water spray or fog, foam or CO₂.
Special Fire Fighting Procedures: Do not enter confined area without proper protective equipment including NIOSH approved self-contained breathing apparatus. Cool fire exposed container and surroundings with water. Product will float on water.
Unusual Fire & Explosion Hazards: Will support combustion when heated above 45°C

SECTION V - HEALTH HAZARD DATA

Route of Entry: Inhalation, skin contact, eye contact, ingestion
Carcinogenic Assessment: This product contains ethylbenzene. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans.
Threshold Limit Value: TWA of 100 ppm based on ACGIH recommendations for Stoddard Solvent
Effects of Overexposure: Inhalation: Slight irritation to mucous membranes
Skin contact: Defatting and drying
Eye contact: Slight eye irritation, increasing with prolonged exposure
Ingestion: May cause vomiting
Emergency & First Aid Procedures: Inhalation: Remove to fresh air. Provide oxygen if breathing is difficult. Administer artificial respiration if breathing has stopped. Get immediate medical attention.
Skin contact: Wash with soap and water. If irritation persists, get medical attention.
Eye contact: Flush with water for 15 minutes. If irritation persists, get medical attention.
Ingestion: DO NOT INDUCE VOMITING. Keep patient at rest. Get immediate medical attention.

SECTION VI - REACTIVITY DATA

Stability: Stable
Incompatibility (Materials to Avoid): Strong oxidizers
Hazardous Decomposition Products: None identified
Hazardous Polymerization: Will not occur

SECTION VII - SPILL OR LEAK PROCEDURE

Steps To Be Taken In Case Material Is Released Or Spilled: Eliminate possible sources of ignition. Dike and contain. Remove by suction, or absorb on clay or vermiculite. Place in labeled drums for disposal.
Waste Disposal Method: Dispose of in accordance with all local, state, and federal regulations. Empty container and allow to air-dry before discarding in an authorized local, state or federal landfill.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: NIOSH-approved respirator or air-purifying respirator for organic vapor.
Ventilation: Explosion-proof for confined spaces to control vapor concentrations.
Protective Gloves: Latex or vinyl
Eye Protection: Safety glasses or goggles
Other Protective Equipment: Splash aprons and/or rubber boots may be desired

SECTION IX - SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storing: Store in original containers for up to 1 year. Keep closed when not in use. Protect from extreme heat and cold.
Other Precautions: Keep out of reach of children. Avoid sparks or open flames. Read and follow label directions.
DOT Hazard Classification: Not regulated